

SON 28 15 disc, SON 28 15 110 disc SON 28 15 150, additional notes

SON 28 15 models for 15 mm suspension forks are designed for off-road use, but not for Downhill biking.

Dimensions and electrical properties correspond with standard SON 28 disc 6-bolt. Please follow the SON 28 instructions with regard to lacing wheels, connecting headlights and rear lights as well as care and maintenance.

SON 28 15 models are made with hollow axles of 15 mm inner diameter as opposed to standard SON 28 that has a hollow axle for quick release mount. The hubs are available in OLD 100 mm, 110 mm and 150 mm.

Fix the hub in the fork with the axle that belongs to the fork in the same way as you do with a hub without dynamo according to the instructions of the fork manufacturer. Just mind a suitable direction of the connections. The well-mounted hub must fit tightly in the fork. If not so, you will hear a rattling noise when spinning the wheel.

Radial spoke lacing is not permitted.

SON 28 15 disc, SON 28 15 110 disc SON 28 15 150, additional notes

SON 28 15 models for 15 mm suspension forks are designed for off-road use, but not for Downhill biking.

Dimensions and electrical properties correspond with standard SON 28 disc 6-bolt. Please follow the SON 28 instructions with regard to lacing wheels, connecting headlights and rear lights as well as care and maintenance.

SON 28 15 models are made with hollow axles of 15 mm inner diameter as opposed to standard SON 28 that has a hollow axle for quick release mount. The hubs are available in OLD 100 mm, 110 mm and 150 mm.

Fix the hub in the fork with the axle that belongs to the fork in the same way as you do with a hub without dynamo according to the instructions of the fork manufacturer. Just mind a suitable direction of the connections. The well-mounted hub must fit tightly in the fork. If not so, you will hear a rattling noise when spinning the wheel.

Radial spoke lacing is not permitted.

SON 28 15 disc, SON 28 15 110 disc SON 28 15 150, additional notes

SON 28 15 models for 15 mm suspension forks are designed for off-road use, but not for Downhill biking.

Dimensions and electrical properties correspond with standard SON 28 disc 6-bolt. Please follow the SON 28 instructions with regard to lacing wheels, connecting headlights and rear lights as well as care and maintenance.

SON 28 15 models are made with hollow axles of 15 mm inner diameter as opposed to standard SON 28 that has a hollow axle for quick release mount. The hubs are available in OLD 100 mm, 110 mm and 150 mm.

Fix the hub in the fork with the axle that belongs to the fork in the same way as you do with a hub without dynamo according to the instructions of the fork manufacturer. Just mind a suitable direction of the connections. The well-mounted hub must fit tightly in the fork. If not so, you will hear a rattling noise when spinning the wheel.

Radial spoke lacing is not permitted.

SON 28 15 disc, SON 28 15 110 disc SON 28 15 150, additional notes

SON 28 15 models for 15 mm suspension forks are designed for off-road use, but not for Downhill biking.

Dimensions and electrical properties correspond with standard SON 28 disc 6-bolt. Please follow the SON 28 instructions with regard to lacing wheels, connecting headlights and rear lights as well as care and maintenance.

SON 28 15 models are made with hollow axles of 15 mm inner diameter as opposed to standard SON 28 that has a hollow axle for quick release mount. The hubs are available in OLD 100 mm, 110 mm and 150 mm.

Fix the hub in the fork with the axle that belongs to the fork in the same way as you do with a hub without dynamo according to the instructions of the fork manufacturer. Just mind a suitable direction of the connections. The well-mounted hub must fit tightly in the fork. If not so, you will hear a rattling noise when spinning the wheel.

Radial spoke lacing is not permitted.